RECKLI® Stripping Aid K

Topcoat for RECKLI Mould Wax to improve the separation effect

PROPERTIES

RECKLI Stripping Aid K is a liquid, solvent-containing wax mixture. It is used to improve the separation effect of RECKLI Mould Wax. It is free from silicone-based contents.

APPLICATIONS

RECKLI Stripping Aid K is especially used as a releasing agent when making elastic polyurethane moulds of gypsum models in the porcelain and ceramic industry.

Attention!
RECKLI Stripping Aid K is not suitable as a single and only release agent for casting polyuretane materials on gypsum.

TECHNICAL DATA

property	value	method
workable temperature:	+10 °C – +30 °C	
density:	0.82 g/cm³	ISO 2811
solid content:	approx. 20 %	by weight

These data are typical guide values. They are not destined for the generation of specifications.

SURFACE PREPARATION

It is recommended to prepare a gypsum model by a thin coating of shellac. Afterwards, 1 – 2 layers of RECKLI Mould Wax are applied with a soft brush. Each layer has to dry completely.

PROCESSING

To even out possible concentration differences, gently swirl or shake the container before use. Subsequently, RECKLI Stripping Aid K is applied once in a thin layer with a soft brush.

CONSUMPTIOND

Approx. 50 ml/m².

RECKLI GmbH
Industriestraße 36
D-44628 Herne
Tel +49 2323 1706-0
Fax +49 2323 1706-50
info@reckli.de
www.reckli.de

PACKAGING SIZES

Cans: 5 l | l 1 l.

STORAGE

Store in a dry well-ventilated room at room temperature. Do not expose to direct sunlight. Keep away from ignition sources, do not smoke. Opened drums must be closed airtight right after use to prevent flocculation due to continuous evaporation of solvents:

SPECIAL ADVICE

RECKLI Stripping Aid K can partially crystallize when kept at low temperatures. When warmed up to 50 °C in the closed can, all components will resolve again, thus allowing the further usage.

SAFETY

RECKLI Stripping Aid K contains a flammable mixture of hydrocarbons. Provide sufficient ventilation in the working place. Keep away from heat, sparks, open flames or any other ignition sources. Do not smoke! Protect skin and eyes from material splashes. Please consult the relevant safety data sheet and attend to the indications on the label of the package regarding the Dangerous Goods Regulation. This pamphlet is intended solely as an application directive. It does not claim to be binding and valid for all modes of application. A preliminary test under operation conditions is highly recommended.

This issue replaces all previously published pamphlets concerning RECKLI Stripping Aid K, stating them as no longer being valid.

RECKLI GmbH
Industriestraße 36
D-44628 Herne
Tel +49 2323 1706-0
Fax +49 2323 1706-50
info@reckli.de
www.reckli.de