

## RECKLI<sup>®</sup> Si-Thickener Liquid AV

thixotropic agent for addition-curing two-component silicones

RECKLI Si-Thickener  
Liquid AV

Product 03246  
Edition 01/23

### PROPERTIES

RECKLI Si-Thickener Liquid AV is a transparent, viscous liquid with a mild sweet odour.

### APPLICATIONS

RECKLI Si-Thickener Liquid AV allows adjusting the consistency of certain silicones to a thixotropic state for the application in vertical or overhead areas. In particular, these are

- RECKLI Si-Compound 21AV
- RECKLI Si-Compound 26AV
- RECKLI Si-Compound 31AV

#### Attention!

RECKLI Si-Thickener Liquid AV is not suitable for condensation-curing silicones. For these ones use RECKLI Si-Thickener Liquid K instead.

### TECHNICAL DATA

| property              | value             | method   |
|-----------------------|-------------------|----------|
| workable temperature: | +10 °C – +30 °C   |          |
| viscosity:            | approx. 500 mPa·s | ISO 2555 |
| dosage:               | 0,1 – 1 %         |          |

These data are typical guide values. They are not destined for the generation of specifications.

### PROCESSING

RECKLI Si-Thickener Liquid AV is added after mixing the base component and the hardener of the relevant silicone material. It is thoroughly stirred in until the demanded consistency is achieved. The resultant paste can be applied to vertical areas up to a total thickness of approximately 5 mm in a single step without running or dripping.

### CLEANING OF EQUIPMENT

For the cleaning of the tools and the equipment, use dry, absorbing cloths, if necessary RECKLI EK-PU Thinner in addition. Immersion in solvents is not

RECKLI GmbH

Industriestraße 36  
D-44628 Herne  
Tel +49 2323 1706-0  
Fax +49 2323 1706-50  
info@reckli.de  
www.reckli.de

sufficient. When cured, the silicone can be removed from the tools due to the self-releasing effect.

### PACKAGING SIZES

bottles: 1 kg | 100 g | 20 g.

RECKLI Si-Thickener  
Liquid AV

Product 03246  
Edition 01/23

### STORAGE

Store in a dry place at room temperature. RECKLI Si-Thickener Liquid AV is storable for 6 months from delivery when kept in the closed original packaging at about 18 °C. Opened bottles must be closed airtight right after use.

### GENERAL INFORMATION

For further information please also see:

„General advice for making moulds and models using RECKLI two-component silicones”.

### SAFETY

Protect skin and eyes from material splashes. Provide sufficient ventilation in the working place. Please consult the relevant safety data sheet and attend to the indications on the label of the package regarding the Dangerous Goods Regulation. This pamphlet is intended solely as an application directive. It does not claim to be binding and valid for all modes of application. A preliminary test under operation conditions is highly recommended.

This pamphlet replaces all previously published pamphlets concerning RECKLI Si-Thickener Liquid AV, stating them as no longer being valid.