

## RECKLI<sup>®</sup> Standardizer 100

RECKLI Standardizer 100

Product 07090

Edition 01/23

mineral thixotropic agent for epoxy resins and polyurethanes

### PROPERTIES

RECKLI Standardizer 100 is a lightweighted, bright mineral powder.

### APPLICATIONS

RECKLI Standardizer 100 is used for thickening RECKLI two-component epoxy resins and polyurethane elastomers. It allows adjusting a pasty state for the application on vertical or overhead areas. When properly mixed, RECKLI Standardizer 100 does not effect inaccurate curing of the thickened material.

### PROCESSING

RECKLI Standardizer 100 is preferably added to the mixed two-component materials rather than to the base component before mixing. Thereby the formation of clumps should be avoided. For mixing, a slow speed drill and agitator paddle is preferably used. The recommended dosage is 0,5 – 20 %, depending on the required consistency.

### PACKAGING SIZES

drums: 3 kg | cans: 200 g.

### STORAGE

Store in a dry place at room temperature. Opened drums must be closed airtight right after use.

### SAFETY

Breathing dust may provoke respiratory irritations. Avoid whirling up the material, provide sufficient ventilation in the working place. Please consult the relevant safety data sheet. This pamphlet is intended solely as an application directive. It does not claim to be binding and valid for all modes of application. A preliminary test under operation conditions is highly recommended.

This pamphlet replaces all previously published pamphlets concerning RECKLI Standardizer 100, stating them as no longer being valid.

RECKLI GmbH

Industriestraße 36

D-44628 Herne

Tel +49 2323 1706-0

Fax +49 2323 1706-50

info@reckli.de

www.reckli.de