

TECHNICAL PAMPHLET

RECKLI[®] Filler C

RECKLI Filler C

Product 07478

Edition 01/23

anorganic filler

PROPERTIES AND APPLICATIONS

RECKLI Filler C is a bright, fine, oven-dry chalk powder. It is suitable for mixing with RECKLI two-component polyurethanes and epoxy resins. RECKLI Filler C is very easily stirred in without lump formation, allowing good flowability of the mixture due to its grain structure. The filling level is depending on the relevant resin's viscosity and must be established under operating conditions in a preliminary test.

PROCESSING

RECKLI Filler C is stirred into the resin with a slow running agitator, preferably after mixing the base component with the hardener.

PACKAGING SIZES

bags: 25 kg;

buckets: 12 kg | 6 kg;

cans: 1 kg.

STORAGE

Store in a dry place. Opened drums must be closed airtight right after use.

GENERAL ADVICE

Please always observe these directions along with the relevant technical pamphlets of the products in question.

SAFETY

Avoid formation of dust. Please consult the relevant safety data sheet. This pamphlet is intended solely as an application directive. It does not claim to be binding and valid for all modes of application. A preliminary test under operation conditions is highly recommended.

This pamphlet replaces all previously published pamphlets concerning RECKLI Filler C, stating them as no longer being valid.

RECKLI GmbH

Industriestraße 36

D-44628 Herne

Tel +49 2323 1706-0

Fax +49 2323 1706-50

info@reckli.de

www.reckli.de