

PRELIMINARY TECHNICAL PAMPHLET

RECKLI[®] Concrete Remover

RECKLI Concrete Remover

Product 04423

Edition 01/23

acidic cleaner for the removal of dried out concrete residues

PROPERTIES

RECKLI Concrete Remover is an acidic, aqueous cleanser for the removal of encrusted concrete splashes. Likewise, it can be used for oily or greasy concrete residues. The use of appropriate equipment allows the application without forming mists or aerosols. The organic contents are readily biodegradable.

APPLICATIONS

RECKLI Concrete Remover is applied for cleaning shutterings, construction machines, tools and equipment after use.

TECHNICAL DATA

property	value	method
colour:	colourless	
odour:	faint	
workable temperature:	+10 °C – +30 °C	
density:	approx. 1,0 g/cm ³	ISO 2811
consumption:	approx. 150 g/m ²	

These data are typical guide values. They are not destined for the generation of specifications.

PROCESSING

Before using RECKLI Concrete Remover, we strongly recommend a preliminary test on an unobtrusive spot to exclude, that the surface might be affected. Only use the cleanser at moderate ambient conditions. Avoid application in case of frost or rain or on hot surfaces.

RECKLI Concrete Remover is delivered ready for use and is applied undiluted with a foam nozzle. The concrete remnants are fully and evenly covered for 15 minutes. Then the loosened material is washed off with a hard water jet (high-pressure cleaner). For stubborn contamination the treatment is repeated if necessary.

To avoid formation of mists and aerosols and to ensure highest effectiveness, the use of a foam nozzle is essential. Additionally, while the treated area can be well discerned, the completeness of processing is easily observed.

RECKLI GmbH

Industriestraße 36

D-44628 Herne

Tel +49 2323 1706-0

Fax +49 2323 1706-50

info@reckli.de

www.reckli.de

CLEANING OF EQUIPMENT

The cleaned surfaces and the tools are thoroughly washed with plenty of water. Metal parts are subsequently protected against corrosion.

RECKLI Concrete Remover

Product 04423

Edition 01/23

CONSUMPTION

approx. 150 g/m² per application (depending on the grade of contamination)

PACKAGING SIZES

canisters: 25 kg | 5 kg

drums: 200 kg.

STORAGE

Store in a well ventilated, dry place at room temperature. RECKLI Concrete Remover is storable for 12 months from delivery when kept in the closed original packaging at about 18 °C. Opened drums must be closed airtight right after use.

Attention! Protect from frost! Never transfer into metal containers!

SAFETY

RECKLI Concrete Remover contains acids. Avoid breathing of mist, vapours or spray. Protect skin, eyes and clothing from material splashes. Provide sufficient ventilation in the working place. When using this product, always wear protective clothing and eye protection. After contact with the skin or the eyes, wash cautiously with water and immediately consult a doctor. Please consult the relevant safety data sheet and attend to the indications on the label of the package regarding the Dangerous Goods Regulation.

This pamphlet is intended solely as an application directive. It does not claim to be binding and valid for all modes of application. A preliminary test under operation conditions is highly recommended.

This pamphlet replaces all previously published pamphlets concerning RECKLI Concrete Remover, stating them as no longer being valid.

RECKLI GmbH

Industriestraße 36

D-44628 Herne

Tel +49 2323 1706-0

Fax +49 2323 1706-50

info@reckli.de

www.reckli.de